

PIC Statement

Vendor Name: Touch-Plate® Lighting Controls
 Product Name: Aura Interior Sensor
 Product Model Number: AUR-IB-FX
 Applications Software Version: 1.5d
 Firmware Revision: 2.48
 BACnet Protocol Revision: 7 (135-2008)

Product Description:

This unit is a general purpose interior sensor that are mapped to Binary Input Objects.

The inputs support subscribed and unsubscribed Change Of Value (COV) operation. MS/TP MAC address, baud rate, I/O configuration may be set using DIP switches.

BACnet Standardized Device Profile (Annex L):

BACnet Application Specific Controller (B-ASC)

BACnet Interoperability Building Blocks Supported (Annex K):

DS-RP-B, DS-RPM-B, DS-WP-B, DS-WPM-B, DS-COV-B, DM-DDB-B, DM-DOB-B, DM-DCC-B, DM-RD-B

Segmentation Capability: Not supported

Standard Object Types Supported:

STANDARD OBJECT TYPES SUPPORTED				
Object	Create	Delete	Optional Properties	Custom Properties
Binary Input	N	N	DEVICE_TYPE, RELIABILITY, INACTIVE_TEXT, ACTIVE_TEXT	---
Analog Value	N	N	---	---

DataLink Layer Options: MS/TP master, baud rate(s): 9600, 19200, 38400, 76800

Device Address Binding: Is static device binding supported? No

Networking Options: No routing or BBMD functions are supported.

Character Sets Supported: ANSI X3.4

